



Alfa Laval Access Tank Cover – Oval Cover Type LKD 440 x 320

High-quality oval manhole tank cover for hygienic applications

Introduction

The Alfa Laval Access Tank Cover – Oval Cover Type LKD 440 x 320 is a stainless steel tank cover that provides a secure fit for openings of tanks or containers. It is engineered for use on the side of tanks or vessels in hygienic applications.

Application

The Access Tank Cover – Oval Cover Type LKD 440 x 320 is designed for use in hygienic applications across for the food, beverage, personal care and wine industries. It is especially suitable for tanks used for the production of wine and juice.

Benefits

- Versatility to cover all tank needs
- Hygienic design
- Available as a 3-A approved version

Standard design

The construction of Access Tank Cover – Oval Cover Type LKD 440 x 320 enables visual inspection into the tank. The tank cover swings outwards and can be positioned above or below the liquid level to meet different application requirements.

Available in standard and pressure models for use both above and below the liquid level, the tank cover complies with the U.S. Food and Drug Administration (FDA) and the European 1935/2004/EC Declarations of Conformity.

Working principle

Open the cover by loosening the handle. For inspection purposes, the cover can then be turned into the tank. If physical entry into the tank is required, the cover can either be removed at the double hinge or swung out of the tank, depending on the model. Hygienically positioned, the seal is not affected by positive or negative pressure in the tank.

Certificates

3.1 (cover and frame are supplied with material certificate 3.1 according to EN10204)



TECHNICAL DATA

Pressure

Max. static pressure:	1.5 bar (150 kPa)
Max. positive working pressure:	0 bar (0 kPa)
Max. negative working pressure:	0.5 bar (50 kPa)
Test pressure:	2.25 bar (225 kPa)

PHYSICAL DATA

Materials

Steel parts:	1.4301 (304) or 1.4404 (316L)
Plastic parts:	Nylon
Seals (FDA):	EPDM, NBR, FPM or Q (silicone)

Standard surface finish:

Product wetted surfaces:	Acid Pickled
Other lid and frame surfaces:	Ra 0.8µm
External support and spindle:	Ra 3.0µm

3A surface finish:


Product wetted surfaces:	Electropolished
Other lid and frame surfaces:	Ra 0.8µm (0.4µm lid wetted surface)
External support and spindle:	Ra 3.0µm

Temperature

Temperature range:	-50°C / 200°C (Q)
Temperature range:	-15°C / 90°C (EPDM)
Temperature range:	-10°C / 250°C (FPM)
Temperature range:	-30°C / 110°C (NBR)

Weight:	7.8 kg
---------	--------

Dimensions (mm)



Type	LKD 440 x 320
A	440
B	320
E	160
F	60
t	8
Cover thickness	2

Alfa Laval reserves the right to change specifications without prior notification.

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.com to access the information direct.